UNITED STATES PATENT AND TRADEMARK OFFICE **CERTIFICATE OF CORRECTION**

PATENT NO.

: 7,017,886 B1

Page 1 of 7

DATED

APPLICATION NO.: 10/802302

INVENTOR(S)

: March 28, 2006 : Ngene-Igwe

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Drawing sheets, consisting of Figs. 1-6c should be deleted to be replaced with the drawing sheets consisting of Figs. 1-6c, as shown on the attached pages.

Illustrative figure on the title page should be deleted and replaced with Fig. 1, as shown on the attached page.

Signed and Sealed this

Fourteenth Day of November, 2006



JON W. DUDAS Director of the United States Patent and Trademark Office



(12) United States Patent Ngene-Igwe

(10) Patent No.:

US 7,017,886 B1

(45) Date of Patent:

Mar. 28, 2006

(54)	SLIDING GATE VALVE			
(76)	Inventor:	Romanus Aniekezie Ngene-Igwe, 2496 McGuffey Rd., Columbus, OH (US) 43211		
(*)	Notice:	Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 33 days.		
(21)	Appl. No.: 10/802,302			
(22)	Filed:	Mar. 17, 2004		
(51)	Int. Cl. F16K 3/00	(2006.01)		
(52)	U.S. CL	251/326		
	Field of Classification Search 251/326-329 See application file for complete search history.			
(56)		References Cited		

U.S. PATENT DOCUMENTS

4,210,308 A *	7/1980	Sims 251/31
4,331,268 A *		Chisholm 222/361
6,375,157 BI	4/2002	Van de Lande 251/327
6,655,660 B1	12/2003	Wales 251/319
6,712,789 Bi	3/2004	Lange et al 604/164.02


* cited by examiner

Primary Examiner—J. Casimer Jacyns
(74) Auorney, Agent, or Firm—Standley Law Group LLP

(57) ABSTRACT


A sliding gate valve, a sealing gasket for the valve, and a method of assembling the valve that may be used to govern the flow of a fluid such as a liquid or a gas. The sealing gasket may be characterized as having a circular portion, two connector portions, and a substantially curved portion that provides a seal discouraging fluid loss during use of the valve. Example fluids suitable for use with the valve include water, air, or oxygen. The fluids may or may not be presurized as the valve provides a seal against leakage that is not dependent upon a pressure differential. Typical installations for the valve include, but are not limited to, household water supply systems, laboratory environments, and industrial settings.


20 Claims, 5 Drawing Sheets



Mar. 28, 2006


Sheet 1 of 5





Mar. 28, 2006

Sheet 2 of 5







Fig. 3a



Mar. 28, 2006

Sheet 3 of 5




Fig. 4a

Fig. 4

Mar. 28, 2006

Sheet 4 of 5




Fig. 5a



Fig. 5b




Fig. 5c




Fig. 5d

Mar. 28, 2006

Sheet 5 of 5




Fig. 6a




Fig. 6b




Fig. 6c